

SAFETY JOGGER

INDUSTRIAL

FOOD

GUSTO S2

Fashionable safety shoe, designed for the food industry

| | |
|-----------------|---|
| Upper | Nappa Action Leather |
| Outsole | PU/PU |
| Toecap | Steel |
| Midsole | Steel |
| Lining | Mesh |
| Footbed | SJ foam footbed |
| Safety category | EN ISO 20345 - S2 / SRC |
| Sample weight | 0.552 gr. |
| Size range | EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 / CM 23.0-31.0 |



013



STEEL TOECAP

Robust metal support to protect the feet of the wearer against falling or rolling objects.



SRC SLIP RESISTANCE

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.




WATER RESISTANT UPPER (WRU)

Prevents penetration of water if not permanently exposed to high levels.



OIL & FUEL RESISTANT

The outsole is resistant against oil and fuel.



HEEL ENERGY ABSORPTION

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



ANTISTATIC

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm

SAFETY JOGGER
WORKS

INDUSTRIAL PROFESSIONAL TACTICAL

WWW.SAFETYJOGGER.COM

ENGINEERED
IN EUROPE



SAFETY JOGGER

INDUSTRIAL

FOOD

GUSTO S2

Industries:

Catering, Cleaning, Construction, Food & beverages, Industry, Medical

Environments:

Dry environment, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



| | Description | Measure unit | Result | EN ISO 20345 |
|----------------|--|-----------------------|--------|--------------|
| Upper | Nappa Action Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 2.25 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 25 | ≥ 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 67.6 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 541 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance | cycles | 400 | ≥ 400 |
| Outsole | PU/PU | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 51.7 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.30 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.34 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.19 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.22 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 106 | 0.1 - 1000 |
| | ESD value | MegaOhm | NA | 0.1 - 100 |
| | Heel energy absorption | J | 30 | ≥ 20 |
| Toecap | Steel | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | NA | ≥ 14 |
| | Compression resistance toecap (clearance after compression 10kN) | mm | NA | ≥ 14 |
| | Impact resistance toecap (clearance after impact 200J) | mm | 14.0 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 16.0 | ≥ 14 |

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:
42

SAFETY JOGGER
WORKS

INDUSTRIAL PROFESSIONAL TACTICAL

WWW.SAFETYJOGGER.COM

ENGINEERED
IN EUROPE